


# UI39 <sup>10,2</sup><sub>14.0VA</sub>

UI39 / 10,2 - 14.0 VA





Temperature class ta 70°C/B

Cul weight : 130 gr

Total weight: 320 gr

Manufactured in according to VDE 0570 and EN 61558 norms

\* Durable to Surge Resistance

SIPARIS KODU / Order No.	PRIMER [V] / Primary	SEKONDER [V] / Secondary	AKIM [mA] / Current	PIM ARALIGI / Pim Configuration	BOSTAKI VOLTAJI [V] / No-Load Voltage
ASL 651206	2x115	2x6	2x1166	1-4 + 7-10 / 11-13 + 18-20	2x7,20
ASL 651208	2x115	2x7,5	2x933	1-4 + 7-10 / 11-13 + 18-20	2x9,00
ASL 651209	2x115	2x9	2x777	1-4 + 7-10 / 11-13 + 18-20	2x10,60
ASL 651212	2x115	2x12	2x583	1-4 + 7-10 / 11-13 + 18-20	2x13,90
ASL 651215	2x115	2x15	2x466	1-4 + 7-10 / 11-13 + 18-20	2x17,80
ASL 651218	2x115	2x18	2x388	1-4 + 7-10 / 11-13 + 18-20	2x21,00
ASL 651224	2x115	2x24	2x291	1-4 + 7-10 / 11-13 + 18-20	2x28,60